

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



Version: 2
Revision date: 22/09/2018

Page 1 of 20
Print date: 22/09/2018

SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: KCS Mayan Gold
Product Code: KCS-MG

1.2 Relevant identified uses of the mixture and uses advised against.

Solvent-based colors for airbrush painting

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **CUSTOM CREATIVE**
Address: C/ SEVILLA 43
City: JEREZ DE LA FRONTERA
Province: CADIZ
Telephone: (+34) 956045939
E-mail: info@customcreative.es
Web: customcreative.es

1.4 Emergency telephone number: (+34) 956045939 (Only available during office hours; Monday-Friday; 08:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

Aquatic Chronic 2 : Toxic to aquatic life with long lasting effects.

Eye Irrit. 2 : Causes serious eye irritation.

Flam. Liq. 2 : Highly flammable liquid and vapour.

STOT SE 3 : May cause drowsiness or dizziness.

Skin Irrit. 2 : Causes skin irritation.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

Danger

H statements:

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

P statements:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



KCS-MG-KCS Mayan Gold

Version: 2
Revision date: 22/09/2018

Page 2 of 20
Print date: 22/09/2018

P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P405	Store locked up.
P501	Dispose of contents/container to ...

Contains:
butanone,ethyl methyl ketone
n-butyl acetate

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
Index No: 607-025-00-1 CAS No: 123-86-4 EC No: 204-658-1 Registration No: 01-2119485493-29-XXXX	[1] n-butyl acetate	20 - 50 %	Flam. Liq. 3, H226 - STOT SE 3, H336	-
Index No: 606-002-00-3 CAS No: 78-93-3 EC No: 201-159-0 Registration No: 01-2119457290-43-XXXX	[1] butanone,ethyl methyl ketone	20 - 25 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-
Index No: 601-022-00-9 CAS No: 1330-20-7 EC No: 215-535-7 Registration No: 01-2119488216-32-XXXX	[1] xylene (Mixture of isomers)	10 - 25 %	Acute Tox. 4 *, H312 - Acute Tox. 4 *, H332 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315	-
CAS No: 85029-58-9 EC No: 285-083-3	Amines, C10-14-branched and linear alkyl, bis[2-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]benzoato(2-)]chromate(1-)	2.5 - 25 %	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410	-
Index No: 603-004-00-6 CAS No: 71-36-3 EC No: 200-751-6 Registration No: 01-2119484630-38-XXXX	[1] n-butanol, butan-1-ol	0 - 1 %	Acute Tox. 4 *, H302 - Eye Dam. 1, H318 - Flam. Liq. 3, H226 - STOT SE 3, H335 - STOT SE 3, H336 - Skin Irrit. 2, H315	-

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



KCS-MG-KCS Mayan Gold

Version: 2
Revision date: 22/09/2018

Page 3 of 20
Print date: 22/09/2018

Index No: 601-023-00-4 CAS No: 100-41-4 EC No: 202-849-4 Registration No: 01-2119489370-35-XXXX	[1] ethylbenzene	0 - 10 %	Acute Tox. 4 *, H332 - Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - STOT RE 2, H373(órganos de audición)	-
Index No: 607-038-00-2 CAS No: 112-07-2 EC No: 203-933-3 Registration No: 01-2119475112-47-XXXX	[1] 2-butoxyethyl acetate, butylglycol acetate	0 - 2.5 %	Acute Tox. 4 *, H312 - Acute Tox. 4 *, H332	-
Index No: 607-035-00-6 CAS No: 80-62-6 EC No: 201-297-1 Registration No: 01-2119452498-28-XXXX	[1] methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate, methyl methacrylate	0 - 1 %	Flam. Liq. 2, H225 - STOT SE 3, H335 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-
Index No: 601-021-00-3 CAS No: 108-88-3 EC No: 203-625-9 Registration No: 01-2119471310-51-XXXX	[1] toluene	0 - 3 %	Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - Repr. 2, H361d *** - STOT RE 2 *, H373 ** - STOT SE 3, H336 - Skin Irrit. 2, H315	-
Index No: 603-108-00-1 CAS No: 78-83-1 EC No: 201-148-0 Registration No: 01-2119484609-23-XXXX	[1] 2-methylpropan-1-ol, iso-butanol	0 - 1 %	Eye Dam. 1, H318 - Flam. Liq. 3, H226 - STOT SE 3, H335 - STOT SE 3, H336 - Skin Irrit. 2, H315	-

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

* ** *** See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a Community workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



KCS-MG-KCS Mayan Gold

Version: 2
Revision date: 22/09/2018

Page 4 of 20
Print date: 22/09/2018

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

SECTION 5: FIREFIGHTING MEASURES.

The product is Highly inflammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate de-

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



KCS-MG-KCS Mayan Gold

Version: 2
Revision date: 22/09/2018

Page 5 of 20
Print date: 22/09/2018

contaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.
For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
n-butyl acetate	123-86-4	United Kingdom [1]	Eight hours	150	724
			Short term	200	966
		United States [2] (Cal/OSHA)	Eight hours	150	
			Short term	200	
		United States [3] (NIOSH)	Eight hours	150	
			Short term	200	
		United States [4] (OSHA)	Eight hours	150	710
			Short term		
butanone, ethyl methyl ketone	78-93-3	European Union [5]	Eight hours	200	600
			Short term	300	900
		United Kingdom [1]	Eight hours	200	600
			Short term	300	899
		United States [2] (Cal/OSHA)	Eight hours	200	
			Short term	300	
		United States [3] (NIOSH)	Eight hours	200	
			Short term	300	
United States	Eight hours	200	590		

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



KCS-MG-KCS Mayan Gold

Version: 2
Revision date: 22/09/2018

Page 6 of 20
Print date: 22/09/2018

xylene (Mixture of isomers)	1330-20-7	[4] (OSHA)	Short term		
		European Union [5]	Eight hours	50 (skin)	221 (skin)
		United Kingdom [1]	Short term	100 (skin)	442 (skin)
			Eight hours	50	220
n-butanol, butan-1-ol	71-36-3	United Kingdom [1]	Short term	100	441
			Eight hours		
		United States [2] (Cal/OSHA)	Short term	50	154
			Eight hours	(Ceiling) 50	
		United States [3] (NIOSH)	Short term	(Ceiling) 50	
			Eight hours		
		United States [4] (OSHA)	Short term	100	300
			Eight hours		
ethylbenzene	100-41-4	European Union [5]	Short term	100 (skin)	442 (skin)
			Eight hours	200 (skin)	884 (skin)
		United Kingdom [1]	Short term	100	441
			Eight hours	125	552
		United States [2] (Cal/OSHA)	Short term	5	
			Eight hours	30	
		United States [3] (NIOSH)	Short term	100	
			Eight hours	125	
United States [4] (OSHA)	Short term	100	435		
	Eight hours				
2-butoxyethyl acetate, butylglycol acetate	112-07-2	European Union [5]	Short term	20 (skin)	133 (skin)
			Eight hours	50 (skin)	333 (skin)
		United Kingdom [1]	Short term	20	133
			Eight hours	50	332
methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate, methyl methacrylate	80-62-6	European Union [5]	Short term	50	
			Eight hours	100	
		United Kingdom [1]	Short term	50	208
			Eight hours	100	416
		United States [2] (Cal/OSHA)	Short term	50	
			Eight hours	100	
		United States [3] (NIOSH)	Short term	100	
			Eight hours		
United States [4] (OSHA)	Short term	100	410		
	Eight hours				
toluene	108-88-3	European Union [5]	Short term	50 (skin)	192 (skin)
			Eight hours	100 (skin)	384 (skin)
		United Kingdom [1]	Short term	50	191
			Eight hours	100	384
		United States [2] (Cal/OSHA)	Short term	10	
			Eight hours	150 (Ceiling) 500	
		United States [3] (NIOSH)	Short term	100	
			Eight hours	150	
		United States [4] (OSHA)	Short term	200	
			Eight hours	300 Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift: 500 [10 min]	
2-methylpropan-1-ol, iso-butanol	78-83-1	United Kingdom [1]	Short term	50	154
			Eight hours	75	231
		United States	Eight hours	50	

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



KCS-MG-KCS Mayan Gold

Version: 2
Revision date: 22/09/2018

Page 7 of 20
Print date: 22/09/2018

		[2] (Cal/OSHA)	Short term		
		United States	Eight hours	50	
		[3] (NIOSH)	Short term		
		United States	Eight hours	100	300
		[4] (OSHA)	Short term		

[1] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

[2] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[3] According Compendium of Policy Documents and Statements adopted by National Institute for Occupational Safety and Health (NIOSH).

[4] According Occupational Health and Safety Standards and US Code of Federal Regulations adopted by US Occupational Safety and Health Administration (OSHA).

[5] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
n-butyl acetate CAS No: 123-86-4 EC No: 204-658-1	DNEL (Workers)	Inhalation, Long-term, Systemic effects	480 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Systemic effects	102,34 (mg/m ³)
	DNEL (Workers)	Inhalation, Acute, Systemic effects	960 (mg/m ³)
	DNEL (General population)	Inhalation, Acute, Systemic effects	859,7 (mg/m ³)
	DNEL (Workers)	Inhalation, Long-term, Local effects	480 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Local effects	102,34 (mg/m ³)
	DNEL (Workers)	Inhalation, Acute, Local effects	960 (mg/m ³)
	DNEL (General population)	Inhalation, Acute, Local effects	859,7 (mg/m ³)
	DNEL (General population)	Oral, Long-term, Systemic effects	3,4 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	3,4 (mg/kg bw/day)
butanone,ethyl methyl ketone CAS No: 78-93-3 EC No: 201-159-0	DNEL (Workers)	Inhalation, Long-term, Systemic effects	600 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Systemic effects	106 (mg/m ³)
	DNEL (Workers)	Dermal, Long-term, Systemic effects	1161 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	412 (mg/kg bw/day)
	DNEL (General population)	Oral, Long-term, Systemic effects	31 (mg/kg bw/day)
	DMEL (General population)	Inhalation, Long-term, Systemic effects	106 (mg/m ³)
	DMEL (General population)	Dermal, Long-term, Systemic effects	412 (mg/m ³)
xylylene (Mixture of isomers) CAS No: 1330-20-7 EC No: 215-535-7	DNEL (Workers)	Inhalation, Long-term, Systemic effects	77 (mg/m ³)
n-butanol, butan-1-ol CAS No: 71-36-3 EC No: 200-751-6	DNEL (Workers)	Inhalation, Long-term, Local effects	310 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Local effects	55 (mg/m ³)

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



KCS-MG-KCS Mayan Gold

Version: 2
Revision date: 22/09/2018

Page 8 of 20
Print date: 22/09/2018

	DNEL (General population)	Oral, Long-term, Systemic effects	3,125 (mg/kg bw/day)
ethylbenzene CAS No: 100-41-4 EC No: 202-849-4	DNEL (Workers)	Inhalation, Long-term, Systemic effects	77 (mg/m ³)
2-butoxyethyl acetate, butylglycol acetate CAS No: 112-07-2 EC No: 203-933-3	DNEL (Workers)	Inhalation, Long-term, Systemic effects	133 (mg/m ³)
methyl 2-methylprop-2-enoate, methyl methylpropenoate, methyl methacrylate CAS No: 80-62-6 EC No: 201-297-1	DNEL (Workers)	Inhalation, Long-term, Local effects	208 (mg/m ³)
	DNEL (Workers)	Inhalation, Long-term, Systemic effects	208 (mg/m ³)
toluene CAS No: 108-88-3 EC No: 203-625-9	DNEL (Workers)	Inhalation, Long-term, Local effects	192 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Local effects	56,5 (mg/m ³)
	DNEL (Workers)	Inhalation, Long-term, Systemic effects	192 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Systemic effects	56,5 (mg/m ³)
	DNEL (Workers)	Inhalation, Acute, Systemic effects	384 (mg/m ³)
	DNEL (General population)	Inhalation, Acute, Systemic effects	226 (mg/m ³)
	DNEL (Workers)	Inhalation, Acute, Local effects	384 (mg/m ³)
	DNEL (General population)	Inhalation, Acute, Local effects	226 (mg/m ³)
	DNEL (Workers)	Dermal, Long-term, Systemic effects	384 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	226 (mg/kg bw/day)
2-methylpropan-1-ol, iso-butanol CAS No: 78-83-1 EC No: 201-148-0	DNEL (Workers)	Inhalation, Long-term, Local effects	310 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Local effects	55 (mg/m ³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
n-butyl acetate CAS No: 123-86-4 EC No: 204-658-1	aqua (freshwater)	0,18 (mg/l)
	aqua (marine water)	0,018 (mg/l)
	aqua (intermittent releases)	0,36 (mg/l)
	PNEC STP	35,6 (mg/l)
	sediment (freshwater)	0,981 (mg/kg sediment dw)
	sediment (marine water)	0,0981 (mg/kg sediment dw)
butanone, ethyl methyl ketone CAS No: 78-93-3	aqua (freshwater)	55,8 (mg/L)
	aqua (marine water)	55,8 (mg/L)

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



KCS-MG-KCS Mayan Gold

Version: 2
Revision date: 22/09/2018

Page 9 of 20
Print date: 22/09/2018

EC No: 201-159-0	Soil	22,5 (mg/kg soil dw)
	aqua (intermittent releases)	55,8 (mg/L)
	PNEC STP	709 (mg/L)
	sediment (freshwater)	284,74 (mg/kg sediment dw)
	sediment (marine water)	284,7 (mg/kg sediment dw)
	oral (Hazard for predators)	1000 (mg/kg food)
n-butanol, butan-1-ol CAS No: 71-36-3 EC No: 200-751-6	aqua (freshwater)	0,082 (mg/L)
	aqua (marine water)	0,0082 (mg/L)
	aqua (intermittent releases)	2,25 (mg/L)
	PNEC STP	2476 (mg/L)
	sediment (freshwater)	0,178 (mg/kg sediment dw)
	sediment (marine water)	0,0178 (mg/kg sediment dw)
toluene CAS No: 108-88-3 EC No: 203-625-9	aqua (freshwater)	0,68 (mg/L)
	aqua (marine water)	0,68 (mg/L)
	aqua (intermittent releases)	0,68 (mg/L)
	PNEC STP	13,61 (mg/L)
	sediment (freshwater)	16,39 (mg/kg sediment dw)
	sediment (marine water)	16,39 (mg/kg sediment dw)
2-methylpropan-1-ol, iso-butanol CAS No: 78-83-1 EC No: 201-148-0	aqua (freshwater)	0,4 (mg/L)
	aqua (marine water)	0,04 (mg/L)
	aqua (intermittent releases)	11 (mg/L)
	STP	10 (mg/L)
	sediment (freshwater)	1,52 (mg/kg sediment dw)
	sediment (marine water)	0,152 (mg/kg sediment dw)
soil	0,0699 (mg/kg soil dw)	

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %
Uses:	Solvent-based colors for airbrush painting
Breathing protection:	
PPE:	Filter mask for protection against gases and particles.
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.
CEN standards:	EN 136, EN 140, EN 405
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.



-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



KCS-MG-KCS Mayan Gold

Version: 2
Revision date: 22/09/2018

Page 10 of 20
Print date: 22/09/2018

Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed:	A2		
Hand protection:			
PPE:	Protective gloves.		
Characteristics:	«CE» marking, category II.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480
		Material thickness (mm):	0,35
Eye protection:			
PPE:	Face shield.		
Characteristics:	«CE» marking, category II. Face and eye protector against splashing liquid.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly.		
Observations:	Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.		
Skin protection:			
PPE:	Anti-static protective clothing.		
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.		
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5		
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.		
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.		
PPE:	Anti-static safety footwear.		
Characteristics:	«CE» marking, category II.		
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346		
Maintenance:	The footwear should be checked regularly		
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.		

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Liquid with characteristic odour
Colour: N.A./N.A.
Odour: N.A./N.A.
Odour threshold: N.A./N.A.
pH: N.A./N.A.
Melting point: N.A./N.A.
Boiling Point: 73 °C
Flash point: 4 °C
Evaporation rate: N.A./N.A.
Inflammability (solid, gas): N.A./N.A.
Lower Explosive Limit: N.A./N.A.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



KCS-MG-KCS Mayan Gold

Version: 2
Revision date: 22/09/2018

Page 11 of 20
Print date: 22/09/2018

Upper Explosive Limit: N.A./N.A.
Vapour pressure: 46,068
Vapour density: N.A./N.A.
Relative density: 0,917
Solubility: N.A./N.A.
Liposolubility: N.A./N.A.
Hydrosolubility: N.A./N.A.
Partition coefficient (n-octanol/water): N.A./N.A.
Auto-ignition temperature: N.A./N.A.
Decomposition temperature: N.A./N.A.
Viscosity: N.A./N.A.
Explosive properties: N.A./N.A.
Oxidizing properties: N.A./N.A.
N.A./N.A. = Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Pour point: N.A./N.A.
Blink: N.A./N.A.
Kinematic viscosity: N.A./N.A.
N.A./N.A. = Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

2-butoxyethanol and its acetate are easily absorbed by the skin and can cause noxious effects to the kidneys.

IRRITANT PREPARATION. Splatters in the eyes can cause irritation.

IRRITANT PREPARATION. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



KCS-MG-KCS Mayan Gold

Version: 2

Revision date: 22/09/2018

Page 12 of 20

Print date: 22/09/2018

n-butyl acetate CAS No: 123-86-4 EC No: 204-658-1	Oral	LD50 Rat 10800 mg/kg bw [1] [1] Acute Toxicity Data. Journal of the American College of Toxicology, Part B. Vol. 1, Pg. 196, 1992
	Dermal	LD50 Rabbit >17600 mg/kg bw [1] [1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 7, 1974
	Inhalation	LC50 Rat 1.85 mg/l/4 h [1] [1] Inhalation Toxicology. Vol. 9, Pg. 623, 1997
butanone,ethyl methyl ketone CAS No: 78-93-3 EC No: 201-159-0	Oral	LD50 Rat 2740 mg/kg bw [1] [1] Toxicology and Applied Pharmacology. Vol. 19, Pg. 699, 1971
	Dermal	LD50 Rabbit 6480 mg/kg bw [1] [1] Shell Chemical Company. Vol. MSDS-5390-4
	Inhalation	
xylene (Mixture of isomers) CAS No: 1330-20-7 EC No: 215-535-7	Oral	LD50 Rat 4300 mg/kg bw [1] [1] AMA Archives of Industrial Health. Vol. 14, Pg. 387, 1956
	Dermal	LD50 Rabbit > 1700 mg/kg bw [1] [1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 123, 1974
	Inhalation	LC50 Rat 21,7 mg/l/4 h [1] [1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 123, 1974
n-butanol, butan-1-ol CAS No: 71-36-3 EC No: 200-751-6	Oral	LD50 Rat 4360 mg/kg bw [1] [1] Union Carbide Corp. Bushy Run Research Center, Project Report No.14-73. Export, PA. 1951.
	Dermal	LD50 Rabbit 3402 mg/kg bw [1] [1] Union Carbide Corp. Bushy Run Research Center, Project Report No.14-73. Export, PA. 1951.
	Inhalation	LC50 Rat 7500 ppm (8 h) [1] [1] Union Carbide Corp. Bushy Run Research Center, Project Report No.14-73. Export, PA. 1951.
ethylbenzene CAS No: 100-41-4 EC No: 202-849-4	Oral	LD50 Rat 3500 mg/kg bw [1] [1] AMA Archives of Industrial Health. Vol. 14, Pg. 387, 1956
	Dermal	LD50 Rabbit 15400 mg/kg bw [1] [1] Food and Cosmetics Toxicology. Vol. 13, Pg. 803, 1975
	Inhalation	
2-methylpropan-1-ol, iso-butanol	Oral	LD50 Rat 2830 mg/kg bw [1] [1] Christopher, S.M. November 30, 1993. "Isobutanol: Acute toxicity and irritancy testing using the rat (peroral and inhalation toxicity) and the rabbit (cutaneous and ocular tests)". Bushy Run Research Center, Union Carbide Corp. Lab. Proj. ID 92U1166
	Dermal	LD50 Rabbit 4240 mg/kg bw [1]

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



KCS-MG-KCS Mayan Gold

Version: 2
Revision date: 22/09/2018

Page 13 of 20
Print date: 22/09/2018

CAS No: 78-83-1	EC No: 201-148-0	Inhalation	[1] Smyth H.F. Jr. et al.: AMA Arch. Ind. Hyg. Occup. Med., 10, 61-68, (1954) as cited in IUCLID.
-----------------	------------------	------------	---

a) acute toxicity;
Not conclusive data for classification.

Acute Toxicity Estimate (ATE):
Mixtures:
ATE (Dermal) = 5.563 mg/kg

b) skin corrosion/irritation;
Product classified:
Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;
Product classified:
Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;
Based on available data, the classification criteria are not met.

e) germ cell mutagenicity;
Not conclusive data for classification.

f) carcinogenicity;
Not conclusive data for classification.

g) reproductive toxicity;
Based on available data, the classification criteria are not met.

h) STOT-single exposure;
Product classified:
Specific target organ toxicity following a single exposure, Category 3:

i) STOT-repeated exposure;
Based on available data, the classification criteria are not met.

j) aspiration hazard;
Based on available data, the classification criteria are not met.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
n-butyl acetate	Fish	LC50	Fish	81 mg/l (96 h) [1]
[1] Wellens, H. 1982. Comparison of the Sensitivity of Brachydanio rerio and Leuciscus idus by Testing the Fish Toxicity of Chemicals and Wastewaters. Z.Wasser-Abwasser-Forsch. 51(2):49-52 (GER) (ENG ABS). Dawson, G.W., A.L. Jennings, D. Drozdowski, and E. Rider 1977. The Acute Toxicity of 47 Industrial Chemicals to Fresh and Saltwater Fishes. J.Hazard.Mater. 1(4):303-318 (OECDG Data File)				

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



KCS-MG-KCS Mayan Gold

Version: 2
Revision date: 22/09/2018

Page 14 of 20
Print date: 22/09/2018

CAS No: 123-86-4 EC No: 204-658-1	Aquatic invertebrates	EC50 Daphnia sp. 44 mg/l (48 h) [1] [1] publication, 1959
	Aquatic plants	EC50 Desmodesmus subspicatus (reported as Scenedesmus subspicatus) 674.7 mg/l (72 h) [1] [1] Method: other: algae growth inhibition test, according to Umweltbundesamt (German Federal Environment Agency) (proposal/draft, version February 1984)
butanone,ethyl methyl ketone CAS No: 78-93-3 EC No: 201-159-0	Fish	LC50 Pimephales promelas 2993 mg/l (96 h) [1] [1] Experimental result, 1998.
	Aquatic invertebrates	LC50 Daphnia magna 8890 mg/l (24 h) [1] [1] Experimental result, 1977.
	Aquatic plants	EC50 Pseudokirchnerella subcapitata 2029 mg/l (96 h) [1] [1] OECD Guideline 201 (Alga, Growth Inhibition Test) reliability based in 2006 guideline.
xylene (Mixture of isomers) CAS No: 1330-20-7 EC No: 215-535-7	Fish	LC50 Fish 15,7 mg/l (96 h) [1] [1] Bailey, H.C., D.H.W. Liu, and H.A. Javitz 1985. Time/Toxicity Relationships in Short-Term Static, Dynamic, and Plug-Flow Bioassays. In: R.C.Bahner and D.J.Hansen (Eds.), Aquatic Toxicology and Hazard Assessment, 8th Symposium, ASTM STP 891, Philadelphia, PA :193-212
	Aquatic invertebrates	LC50 Crustacean 8,5 mg/l (48 h) [1] [1] Tatem, H.E., B.A. Cox, and J.W. Anderson 1978. The Toxicity of Oils and Petroleum Hydrocarbons to Estuarine Crustaceans. Estuar.Coast.Mar.Sci. 6(4):365-373. Tatem, H.E. 1975. The Toxicity and Physiological Effects of Oil and Petroleum Hydrocarbons on Estuarine Grass Shrimp Palaemonetes pugio (Holthuis). Ph.D.Thesis, Texas A&M University, College Station, TX :133 p
	Aquatic plants	
n-butanol, butan-1-ol CAS No: 71-36-3 EC No: 200-751-6	Fish	LC50 Pimephales promelas 1376 mg/L (96 h) [1] [1] Wong, D.C.L, P.B. Dorn, and J.P. Salanitro. 1998. Aquatic Toxicity of Four Oxy-Solvents. Equilon Enterprises, LLC Technical Information Record WTC-3520.
	Aquatic invertebrates	EC50 Daphnia magna 1328 mg/L (48 h) [1] [1] Wong, D.C.L, P.B. Dorn, and J.P. Salanitro. 1998. Aquatic Toxicity of Four Oxy-Solvents. Equilon Enterprises, LLC Technical Information Record WTC-3520.
	Aquatic plants	EC90 Selenastrum capricornutum (Pseudokirchnerella subcapitata) 717 mg/L (96 h) [1] [1] Wong, D.C.L, P.B. Dorn, and J.P. Salanitro. 1998. Aquatic Toxicity of Four Oxy-Solvents. Equilon Enterprises, LLC Technical Information Record WTC-3520.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



KCS-MG-KCS Mayan Gold

Version: 2
Revision date: 22/09/2018

Page 15 of 20
Print date: 22/09/2018

ethylbenzene CAS No: 100-41-4 EC No: 202-849-4	Fish	LC50 Fish 80 mg/l (96 h) [1] [1] Mayer, F.L.Jr., and M.R. Ellersieck 1986. Manual of Acute Toxicity: Interpretation and Data Base for 410 Chemicals and 66 Species of Freshwater Animals. Resour.Publ.No.160, U.S.Dep.Interior, Fish Wildl.Serv., Washington, DC :505 p. (USGS Data File)
	Aquatic invertebrates	LC50 Crustacean 16,2 mg/l (48 h) [1] [1] MacLean, M.M., and K.G. Doe 1989. The Comparative Toxicity of Crude and Refined Oils to Daphnia magna and Artemia. Environment Canada, EE-111, Dartmouth, Nova Scotia :64 p
	Aquatic plants	EC50 Algae 5 mg/l (72 h) [1] [1] Galassi, S., M. Mingazzini, L. Vigano, D. Cesareo, and M.L. Tosato 1988. Approaches to Modeling Toxic Responses of Aquatic Organisms to Aromatic Hydrocarbons. Ecotoxicol.Environ.Saf. 16(2):158-169. Masten, L.W., R.L. Boeri, and J.D. Walker 1994. Strategies Employed to Determine the Acute Aquatic Toxicity of Ethyl Benzene, a Highly Volatile, Poorly Water-Soluble Chemical. Ecotoxicol.Environ.Saf. 27(3):335-348
toluene CAS No: 108-88-3 EC No: 203-625-9	Fish	LC50 Fish 31,7 mg/l (96 h) [1] [1] Geiger, D.L., L.T. Brooke, and D.J. Call 1990. Acute Toxicities of Organic Chemicals to Fathead Minnows (Pimephales promelas), Volume 5. Ctr.for Lake Superior Environ.Stud., Univ.of Wisconsin-Superior, Superior, WI :332 p
	Aquatic invertebrates	LC50 Crustacean 92 mg/l (48 h) [1] [1] MacLean, M.M., and K.G. Doe 1989. The Comparative Toxicity of Crude and Refined Oils to Daphnia magna and Artemia. Environment Canada, EE-111, Dartmouth, Nova Scotia :64 p
	Aquatic plants	EC50 Algae 12,5 mg/l (72 h) [1] [1] Galassi, S., M. Mingazzini, L. Vigano, D. Cesareo, and M.L.Tosato 1988. Approaches to Modeling Toxic Responses of Aquatic Organisms to Aromatic Hydrocarbons. Ecotoxicol.Environ.Saf. 16(2):158-169
2-methylpropan-1-ol,iso-butanol	Fish	EC50 Pimephales promelas 1430 mg/L (96 h h) [1] [1] Brooke, L.T. et al., 1984. Acute Toxicities of Organic Chemicals to Fathead Minnows (Pimephales promelas). Vol. I. Center for Lake Superior Environmental Studies. University of Wisconsin-Superior.
	Aquatic invertebrates	EC50 Daphnia magna 1300 mg/L (48 h) [1] [1] Elnabarawy MT, Welter AN, Robideau RR. 1986. relative sensitivity of three daphnid species to selected organic and inorganic chemicals. Environ Toxicol Chem 5: 393-398.
	Aquatic plants	EC90 Selenastrum capricornutum (Pseudokirchnerella subcapitata) 717 mg/L (96 h) [1]

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



KCS-MG-KCS Mayan Gold

Version: 2
Revision date: 22/09/2018

Page 16 of 20
Print date: 22/09/2018

CAS No: 78-83-1	EC No: 201-148-0	[1] Wong, D.C.L, P.B. Dorn, and J.P. Salanitro. 1998. Aquatic Toxicity of Four Oxy-Solvents. Equilon Enterprises, LLC Technical Information Record WTC-3520.
-----------------	------------------	--

12.2 Persistence and degradability.

There is no information available on the degradability of the substances present.
No information is available regarding the degradability of the substances present.No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
n-butyl acetate N. CAS: 123-86-4 EC No: 204-658-1	1,78	-	-	Very low
butanone,ethyl methyl ketone N. CAS: 78-93-3 EC No: 201-159-0	0,29	-	-	Very low
n-butanol, butan-1-ol N. CAS: 71-36-3 EC No: 200-751-6	0,84	-	-	Very low
ethylbenzene N. CAS: 100-41-4 EC No: 202-849-4	3,15	-	-	Moderate
toluene N. CAS: 108-88-3 EC No: 203-625-9	2,73	-	-	Low
2-methylpropan-1-ol,iso-butanol N. CAS: 78-83-1 EC No: 201-148-0	0,76	-	-	Very low

12.4 Mobility in soil.

No information is available about the mobility in soil.
The product must not be allowed to go into sewers or waterways.
Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13 DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



KCS-MG-KCS Mayan Gold

Version: 2
Revision date: 22/09/2018

Page 17 of 20
Print date: 22/09/2018

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.

Transport document: Airway bill.

14.1 UN number.

UN No: UN1263

14.2 UN proper shipping name.

Description:

ADR: UN 1263, PAINT, 3, PG II, (D/E)

IMDG: UN 1263, PAINT (AMINES, C10-14-BRANCHED AND LINEAR ALKYL, BIS[2-[(4,5-DIHYDRO-3-METHYL-5-OXO-1-PHENYL-1H-PYRAZOL-4-YL)AZO]BENZOATO(2-)]CHROMATE(1-)), 3, PG II, MARINE POLLUTANT

ICAO/IATA: UN 1263, PAINT, 3, PG II

14.3 Transport hazard class(es).

Class(es): 3

14.4 Packing group.

Packing group: II

14.5 Environmental hazards.

Marine pollutant: Yes



Dangerous for the environment

14.6 Special precautions for user.

Labels: 3



Hazard number: 33

ADR LQ: 5 L

IMDG LQ: 5 L

ICAO LQ: 1 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-E

Proceed in accordance with point 6.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



KCS-MG-KCS Mayan Gold

Version: 2
Revision date: 22/09/2018

Page 18 of 20
Print date: 22/09/2018

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)

Product Subcategory (Directive 2004/42/EC): Special finishes (All types)

Phase I* (from 01/01/2007): 840 g/l

Phase II* (from 01/01/2010): 840 g/l

(*) g/l ready to use

VOC content (p/p): 66,694 %

VOC content: 611,556 g/l

The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles:

Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
48. Toluene CAS No 108-88-3 EC No 203-625-9	Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

Kind of pollutant for the water (Germany): WGK 2: Hazardous for the water. (Autoclassified according to the AwSV Regulations)

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



KCS-MG-KCS Mayan Gold

Version: 2
Revision date: 22/09/2018

Page 19 of 20
Print date: 22/09/2018

H373 May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>. (órganos de audición)
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

Classification codes:

Acute Tox. 4 : Acute toxicity (Dermal), Category 4
Acute Tox. 4 : Acute toxicity (Inhalation), Category 4
Acute Tox. 4 : Acute toxicity (Oral), Category 4
Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1
Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1
Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2
Asp. Tox. 1 : Aspiration toxicity, Category 1
Eye Dam. 1 : Serious eye damage, Category 1
Eye Irrit. 2 : Eye irritation, Category 2
Flam. Liq. 2 : Flammable liquid, Category 2
Flam. Liq. 3 : Flammable liquid, Category 3
Repr. 2 : Reproductive toxicant, Category 2
STOT RE 2 : Specific target organ toxicity following a repeated exposure, Category 2
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3
Skin Irrit. 2 : Skin irritant, Category 2
Skin Sens. 1 : Skin sensitiser, Category 1

Sections changed compared with the previous version:

1,4,16

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
AwSV: Facility Regulations for handling substances that are hazardous for the water.
BCF: Bioconcentration factor.
CEN: European Committee for Standardization.
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
EC50: Half maximal effective concentration.
PPE: Personal protection equipment.
IATA: International Air Transport Association.
ICAO: International Civil Aviation Organization.
IMDG: International Maritime Code for Dangerous Goods.
LC50: Lethal concentration, 50%.
LD50: Lethal dose, 50%.
Log Pow: Logarithm of the partition octanol-water.
NOEC: No observed effect concentration.
PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.
WGK: Water hazard classes.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>
<http://echa.europa.eu/>
Regulation (EU) 2015/830.
Regulation (EC) No 1907/2006.
Regulation (EU) No 1272/2008.

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



KCS-MG-KCS Mayan Gold

Version: 2
Revision date: 22/09/2018

Page 20 of 20
Print date: 22/09/2018

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.