(in accordance with Regulation (EU) 2015/830)

KCS-PR-KCS Pink Rose



Version: 2 Revision date: 22/09/2018 Page 1 of 12 Print date: 22/09/2018

SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: KCS Pink Rose Product Code: KCS-PR

1.2 Relevant identified uses of the mixture and uses advised against.

Solvent-based colors for airbrush painting

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company:	CUSTOM CREATIVE
Address:	C/ SEVILLA 43
City:	JEREZ DE LA FRONTERA
Province:	CADIZ
Telephone:	(+34) 956045939
E-mail:	info@customcreative.es
Web:	customcreative.es

1.4 Emergency telephone number: (+34) 956045939 (Only available during office hours; Monday-Friday; 08:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008: Eye Irrit. 2 : Causes serious eye irritation. Flam. Liq. 3 : Flammable liquid and vapour. STOT SE 3 : May cause respiratory irritation.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008: Pictograms:



Signal Word: Warning H statements: H226

H319

H335

Flammable liquid and vapour. Causes serious eye irritation. May cause respiratory irritation.

P statements:

statements.	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P405	Store locked up.

(in accordance with Regulation (EU) 2015/830)

KCS-PR-KCS Pink Rose



Page 2 of 12 Print date: 22/09/2018

Version: 2 Revision date: 22/09/2018

· · · · · · · · · · · · · · ·

P501

Dispose of contents/container to ...

EUH statements: EUH066

Repeated exposure may cause skin dryness or cracking.

Contains: 4-methylpentan-2-one,isobutyl methyl ketone

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification - Regulation (EC) No 1272/2008	
Identifiers	Name	Concentrate	Classification	specific concentration limit
Index No: 607-195- 00-7 CAS No: 108-65-6 EC No: 203-603-9 Registration No: 01- 2119475791-29-XXXX	[1] 2-methoxy-1-methylethyl acetate	25 - 50 %	Flam. Liq. 3, H226	-
Index No: 606-004- 00-4 CAS No: 108-10-1 EC No: 203-550-1 Registration No: 01- 2119473980-30-XXXX	[1] 4-methylpentan-2-one, isobutyl methyl ketone	20 - 25 %	Acute Tox. 4 *, H332 - Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H335	-
CAS No: 1309457-61-	Polymer based on Polyethyleneimine-Polyester- Fattyacid	1 - 2.5 %	Acute Tox. 4, H302 - Aquatic Chronic 2, H411	-

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a Community workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Dont let the person to rub the affected eye.

(in accordance with Regulation (EU) 2015/830)

KCS-PR-KCS Pink Rose



Page 3 of 12 Print date: 22/09/2018

Version: 2 Revision date: 22/09/2018

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

SECTION 5: FIREFIGHTING MEASURES.

Flammable product, the necessary prevention measures should be taken in order to avoid risks, In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

(in accordance with Regulation (EU) 2015/830)

KCS-PR-KCS Pink Rose



Page 4 of 12 Print date: 22/09/2018

Version: 2 Revision date: 22/09/2018

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8. For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use antistatic footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks.For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
		European	Eight hours	50 (skin)	275 (skin)
2-methoxy-1-methylethyl acetate	108-65-6	Union [1]	Short term	100 (skin)	550 (skin)
	100-03-0	United	Eight hours	50	274
		Kingdom [2]	Short term	100	548
		European	Eight hours	20	83
	108-10-1 United States [3] (Cal/OSHA) United States	Union [1]	Short term	50	208
		United	Eight hours	50	208
		Short term	100	416	
4-methylpentan-2-one, isobutyl methyl		United States	Eight hours	50	
ketone		[3] (Cal/OSHA)	Short term	75	
		United States	Eight hours	50	
		[4] (NIOSH)	Short term	75	
		United States	Eight hours	100	410
		[5] (OSHA)	Short term		

(in accordance with Regulation (EU) 2015/830)

KCS-PR-KCS Pink Rose



Page 5 of 12 Print date: 22/09/2018

Version: 2 Revision date: 22/09/2018

[1] According both Binding Occupational Esposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adobted by Health and Safety Executive.

[3] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[4] According Compendium of Policy Documents and Statements adopted by National Institute for Occupational Safety and Health (NIOSH).

[5] According Occupational Health and Safety Standards and US Code of Federal Regulations adopted by US Occupational Safety and Health Administration (OSHA).

The product does NOT contain substances with Biological Limit Values. Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
	DNEL	Inhalation, Long-term, Systemic effects	275
	(Workers)		(mg/m ³)
	DNEL (General	Inhalation, Long-term, Systemic effects	33
	population)		(mg/m ³)
	DNEL	Dermal, Long-term, Systemic effects	153,5
2-methoxy-1-methylethyl acetate	(Workers)		(mg/kg
CAS No: 108-65-6			bw/day)
EC No: 203-603-9	DNEL (General	Dermal, Long-term, Systemic effects	54,8
	population)		(mg/kg
			bw/day)
	DNEL (General	Oral, Long-term, Systemic effects	1,67
	population)		(mg/kg
			bw/day)
	DNEL	Inhalation, Long-term, Local effects	83
	(Workers)		(mg/m ³)
	DNEL (General	Inhalation, Long-term, Local effects	14,7
	population)		(mg/m ³)
	DNEL	Inhalation, Long-term, Systemic effects	83
	(Workers)		(mg/m ³)
	DNEL (General	Inhalation, Long-term, Systemic effects	14,7
	population)		(mg/m ³)
	DNEL	Inhalation, Acute, Systemic effects	208
	(Workers)		(mg/m ³)
4-methylpentan-2-one, isobutyl methyl ketone	DNEL (General	Inhalation, Acute, Systemic effects	155,2
CAS No: 108-10-1	population)		(mg/m ³)
EC No: 203-550-1	DNEL	Inhalation, Acute, Local effects	208
	(Workers)		(mg/m ³)
	DNEL (General	Inhalation, Acute, Local effects	155,2
	population)		(mg/m ³)
	DNEL	Dermal, Long-term, Systemic effects	11,8
	(Workers)		(mg/kg
			bw/day)
	DNEL (General	Dermal, Long-term, Systemic effects	4,2 (mg/kg
	population)		bw/day)
	DNEL (General	Oral, Long-term, Systemic effects	4,2 (mg/kg
	population)		bw/day)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated. DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum. Concentration levels PNEC:

Name	Details	Value
	aqua (freshwater)	0,635 (mg/L)
2-methoxy-1-methylethyl acetate CAS No: 108-65-6	aqua (marine water)	0,0635 (mg/L)
EC No: 203-603-9	aqua (intermittent releases)	6,35 (mg/L)
	PNEC STP	100 (mg/L)

(in accordance with Regulation (EU) 2015/830)

KCS-PR-KCS Pink Rose



Version: 2 Revision date: 22/09/2018 Page 6 of 12 Print date: 22/09/2018

	sediment (freshwater)	3,29 (mg/kg sediment dw)
	sediment (marine water)	0,329 (mg/kg sediment dw)
	soil	0,29 (mg/kg soil dw)
	aqua (freshwater)	0,6 (mg/L)
	aqua (marine water)	0,06 (mg/L)
	aqua (intermittent releases)	1,5 (mg/L)
1 mathulaantan 2 ana isahutul mathul katana	PNEC STP	27,5 (mg/L)
4-methylpentan-2-one,isobutyl methyl ketone CAS No: 108-10-1 EC No: 203-550-1	sediment (freshwater)	8,27 (mg/kg sediment dw)
	sediment (marine water)	0,83 (mg/kg sediment dw)
	soil	1,3 (mg/kg
		soil dw)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %
Uses:	Solvent-based colors for airbrush painting
Breathing protect	ion:
If the recommended	technical measures are observed, no individual protection equipment is necessary.
Hand protection:	
If the product is han	dled correctly, no individual protection equipment is necessary.
Eye protection:	
PPE:	Face shield.
Characteristics:	«CE» marking, category II. Face and eye protector against splashing liquid.
CEN standards:	EN 165, EN 166, EN 167, EN 168
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly.
Observations:	Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.
Skin protection:	
PPE:	Anti-static protective clothing.
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.
PPE:	Anti-static safety footwear.
Characteristics:	«CE» marking, category II.
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346
Maintenance:	The footwear should be checked regularly
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.

(in accordance with Regulation (EU) 2015/830)

KCS-PR-KCS Pink Rose



Version: 2 Revision date: 22/09/2018 Page 7 of 12 Print date: 22/09/2018

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties. Appearance: Liquid with characteristic odour Colour: rojo Odour:N.A./N.A. Odour threshold:N.A./N.A. pH:N.A./N.A. Melting point:N.A./N.A. Boiling Point: 87 °C Flash point: 29 °C Evaporation rate: N.A./N.A. Inflammability (solid, gas): N.A./N.A. Lower Explosive Limit: N.A./N.A. Upper Explosive Limit: N.A./N.A. Vapour pressure: 8,69 Vapour density:N.A./N.A. Relative density:0,96 Solubility:N.A./N.A. Liposolubility: N.A./N.A. Hydrosolubility: N.A./N.A. Partition coefficient (n-octanol/water): N.A./N.A. Auto-ignition temperature: N.A./N.A. Decomposition temperature: N.A./N.A. Viscosity: N.A./N.A. Explosive properties: N.A./N.A. Oxidizing properties: N.A./N.A. N.A./N.A.= Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Pour point: N.A./N.A. Blink: N.A./N.A. Kinematic viscosity: N.A./N.A. N.A./N.A.= Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

If the storage conditions are satisfied, does not produce dangerous reactions.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

Flammable liquid and vapour. At high temperatures can occur pyrolysis and dehydrogenation.

10.4 Conditions to avoid.

Avoid the following conditions:

- Heating.
- High temperature.
- Static discharge.
- Contact with incompatible materials.

- Avoid temperatures near or above the flash point. Do not heat closed containers. Avoid direct sunlight and heat, as these may cause a risk of fire.

10.5 Incompatible materials.

Avoid the following materials:

- Acids.
- Bases.

(in accordance with Regulation (EU) 2015/830)

KCS-PR-KCS Pink Rose



Page 8 of 12 Print date: 22/09/2018

Version: 2 Revision date: 22/09/2018

- Oxidizing agents.
- Explosives materials.
- Toxic materials.
- Oxidizing materials.

10.6 Hazardous decomposition products.

In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT PREPARATION. Splatters in the eyes can cause irritation.

IRRITANT PREPARATION. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

Toxicological information about the substances present in the composition.

Name	Acute toxicity				
Name	Туре	Test	Kind	Value	
	Oral	LD50	Rat	6190 mg/kg bw [1]	
2-methoxy-1-methylethyl acetate		Toxicity).	• •	OECD Guideline 401 (Acute Oral	
	Dermal	LD50	Rabbit	>5000 mg/kg bw [1]	
		[1] Dow Ch	emical Compai	ny Reports. Vol. MSD-1582	
		LC0	Rat	>4345 ppm (6 h) [1]	
CAS No: 108-65-6 EC No: 203-603-9	Inhalation	[1] Study re Inhalation		ECD Guideline 403 (Acute	
	Oral	LD50	Rat	2080 mg/kg bw [1]	
		[1] Union Carbide Data Sheet. Vol. 4/25/1958			
4-methylpentan-2-one, isobutyl methyl ketone		LD0	Rat	>=2000 mg/kg bw [1]	
	Dermal		Guideline 402 (<i>I</i> al result, 1996)	Acute Dermal Toxicity) 1987,	
		LC50	Rat	>2000 <4000 ppm (4 h) [1]	
CAS No: 108-10-1 EC No: 203-550-1	Inhalation		-FINDING TOXI CP & Weil CS, 1	ICITY DATA: LIST IV, Smyth HF,	

a) acute toxicity;

Not conclusive data for classification.

Acute Toxicity Estimate (ATE): Mixtures: ATE (Oral) = 25.000 mg/kg

b) skin corrosion/irritation; Not conclusive data for classification.

c) serious eye damage/irritation; Product classified: Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation; Not conclusive data for classification.

(in accordance with Regulation (EU) 2015/830)

KCS-PR-KCS Pink Rose



Page 9 of 12 Print date: 22/09/2018

Version: 2 Revision date: 22/09/2018

e) germ cell mutagenicity; Not conclusive data for classification.

f) carcinogenicity; Not conclusive data for classification.

g) reproductive toxicity; Not conclusive data for classification.

h) STOT-single exposure; Product classified: Specific target organ toxicity following a single exposure, Category 3:

i) STOT-repeated exposure; Not conclusive data for classification.

j) aspiration hazard; Not conclusive data for classification.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity					
Name	Туре	Test	Kind	Value		
	Fish	LC50	Oryzias latipes	100 mg/L (96 h) [1]		
		[1] Environment Agency of Japan (1998)				
	Aquatic	EC50	Daphnia magna	407 mg/L (48 h) [1]		
2-methoxy-1-methylethyl acetate	invertebrates	[1] Enviror	nment Agency of Japa	an (1998)		
	Aquatic plants	EC50	Selenastrum capricornutum (Pseudokirchnerell a subcapitata)	>1000 mg/L (72 h) [1]		
CAS No: 108-65-6 EC No: 203-603-9		[1] Enviror	nment Agency of Japa	an (1998)		
		LC50	Danio rerio	>179 mg/l (96 h) [1]		
	Fish	[1] Experimental result, April 29 to May 03, 2010.				
4-methylpentan-2-one, isobutyl methyl ketone		EC50	Daphnia magna	1550 mg/l (24 h) [1]		
	Aquatic invertebrates	[1] OECD Test)	Guideline 202 (Daphn	ia sp. Acute Immobilisation		
		EC50	Lemna gibba	>146 mg/l (7 d) [1]		
CAS No: 108-10-1 EC No: 203-550-1	Aquatic plants		report, 2010. OECD G hibition test)	uideline 221 (Lemna sp.		

12.2 Persistence and degradability.

There is no information available on the degradability of the substances present.

No information is available regarding the degradability of the substances present.No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

(in accordance with Regulation (EU) 2015/830)

KCS-PR-KCS Pink Rose



Page 10 of 12 Print date: 22/09/2018

Version: 2 Revision date: 22/09/2018

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
Nallie	Log Pow	BCF	NOECs	Level
4-methylpentan-2-one, isobutyl methyl ketone	1,31	_		Verv low
N. CAS: 108-10-1 EC No: 203-550-1	1,51	-	-	veryiow

12.4 Mobility in soil.

No information is available about the mobility in soil. The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13 DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID. Transport documentation: Consignment note and written instructions Sea: Transport by ship: IMDG. Transport documentation: Bill of lading Air: Transport by plane: ICAO/IATA. Transport document: Airway bill.

14.1 UN number. UN No: UN1263

14.2 UN proper shipping name.

Description: ADR: UN 1263, PAINT, 3, PG III, (D/E) IMDG: UN 1263, PAINT, 3, PG III ICAO/IATA: UN 1263, PAINT, 3, PG III

14.3 Transport hazard class(es).

Class(es): 3

14.4 Packing group.

Packing group: III

14.5 Environmental hazards.

Marine pollutant: No

(in accordance with Regulation (EU) 2015/830)

KCS-PR-KCS Pink Rose



Page 11 of 12 Print date: 22/09/2018

Version: 2 Revision date: 22/09/2018

14.6 Special precautions for user. Labels: 3



Hazard number: 30 ADR LQ: 5 L IMDG LQ: 5 L ICAO LQ: 10 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR. Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-E Proceed in accordance with point 6.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

 $\label{eq:Volatile organic compound (VOC)} \end{tabular} \label{eq:Volatile organic compound (VOC)} \end{tabular} \end{tabular$

VOC content (p/p): 59,5 % VOC content: 571,309 g/l

The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Kind of pollutant for the water (Germany): WGK 1: Slightly hazardous for the water. (Autoclassified according to the AwSV Regulations)

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.

(in accordance with Regulation (EU) 2015/830)

KCS-PR-KCS Pink Rose



Page 12 of 12 Print date: 22/09/2018

version:	2		
Revision	date:	22/09	/2018

H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.

Classification codes:

Acute Tox. 4 : Acute toxicity (Inhalation), Category 4 Acute Tox. 4 : Acute toxicity (Oral), Category 4 Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2 Eye Irrit. 2 : Eye irritation, Category 2 Flam. Liq. 2 : Flammable liquid, Category 2 Flam. Liq. 3 : Flammable liquid, Category 3 STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

Sections changed compared with the previous version:

1,4,16

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
- AwSV: Facility Regulations for handling substances that are hazardous for the water.
- BCF: Bioconcentration factor.
- CEN: European Committee for Standardization.
- DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
- DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
- EC50: Half maximal effective concentration.
- PPE: Personal protection equipment.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.
- IMDG: International Maritime Code for Dangerous Goods.
- LC50: Lethal concentration, 50%.
- LD50: Lethal dose, 50%.
- Log Pow: Logarithm of the partition octanol-water.
- NOEC: No observed effect concentration.
- PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.
- RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.
- WGK: Water hazard classes.

Key literature references and sources for data: http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/ Regulation (EU) 2015/830. Regulation (EC) No 1907/2006. Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.