

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

KLW-55-KANDY LISTO AL USO BASE AGUA - MAGENTA 55



Version: 2
Revision date: 12/02/2018

Page 1 of 13
Print date: 22/09/2018

SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: KANDY LISTO AL USO BASE AGUA - MAGENTA 55
Product Code: KLW-55

1.2 Relevant identified uses of the mixture and uses advised against.

Water base colors for airbrush painting

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **CUSTOM CREATIVE**
Address: C/ SEVILLA 43
City: JEREZ DE LA FRONTERA
Province: CADIZ
Telephone: (+34) 956045939
E-mail: info@customcreative.es
Web: customcreative.es

1.4 Emergency telephone number: (+34) 956045939 (Only available during office hours; Monday-Friday; 08:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

Eye Irrit. 2 : Causes serious eye irritation.
Flam. Liq. 3 : Flammable liquid and vapour.
Skin Irrit. 2 : Causes skin irritation.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

Warning

H statements:

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

P statements:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P370+P378	In case of fire: Use... to extinguish.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

KLW-55-KANDY LISTO AL USO BASE AGUA - MAGENTA 55



Version: 2
Revision date: 12/02/2018

Page 2 of 13
Print date: 22/09/2018

P501 Dispose of contents/container to ...

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
Index No: 603-014-00-0 CAS No: 111-76-2 EC No: 203-905-0 Registration No: 01-2119475108-36-XXXX	[1] 2-butoxyethanol, butyl cellosolve, ethylene glycol monobutyl ether	1 - 10 %	Acute Tox. 4 *, H312 - Acute Tox. 4 *, H332 - Acute Tox. 4 *, H302 - Eye Irrit. 2, H319 - Skin Irrit. 2, H315	-
Index No: 603-004-00-6 CAS No: 71-36-3 EC No: 200-751-6 Registration No: 01-2119484630-38-XXXX	[1] n-butanol, butan-1-ol	1 - 3 %	Acute Tox. 4 *, H302 - Eye Dam. 1, H318 - Flam. Liq. 3, H226 - STOT SE 3, H335 - STOT SE 3, H336 - Skin Irrit. 2, H315	-
Index No: 603-096-00-8 CAS No: 112-34-5 EC No: 203-961-6 Registration No: 01-2119475104-44-XXXX	[1] 2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	0 - 10 %	Eye Irrit. 2, H319	-
Index No: 606-002-00-3 CAS No: 78-93-3 EC No: 201-159-0 Registration No: 01-2119457290-43-XXXX	[1] butanone, ethyl methyl ketone	0 - 10 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-
Index No: 603-047-00-0 CAS No: 108-01-0 EC No: 203-542-8 Registration No: 01-2119492298-24-XXXX	[1] N,N-dimethylethanolamine, 2-dimethylaminoethanol	0 - 1 %	Acute Tox. 4 *, H312 - Acute Tox. 4 *, H332 - Acute Tox. 4 *, H302 - Flam. Liq. 3, H226 - Skin Corr. 1B, H314	STOT SE 3, H335: C ≥ 5 %

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a Community workplace exposure limit (see section 8.1).

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

KLW-55-KANDY LISTO AL USO BASE AGUA - MAGENTA 55



Version: 2
Revision date: 12/02/2018

Page 3 of 13
Print date: 22/09/2018

SECTION 4: FIRST AID MEASURES.

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

SECTION 5: FIREFIGHTING MEASURES.

Flammable product, the necessary prevention measures should be taken in order to avoid risks, In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

Fire protection equipment.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

KLW-55-KANDY LISTO AL USO BASE AGUA - MAGENTA 55



Version: 2
Revision date: 12/02/2018

Page 4 of 13
Print date: 22/09/2018

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
------	---------	---------	-------------	-----	-------------------

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



KLW-55-KANDY LISTO AL USO BASE AGUA - MAGENTA 55

Version: 2
Revision date: 12/02/2018

Page 5 of 13
Print date: 22/09/2018

2-butoxyethanol, butyl cellosolve, ethylene glycol monobutyl ether	111-76-2	European Union [1]	Eight hours	20 (skin)	98 (skin)
			Short term	50 (skin)	246 (skin)
		United Kingdom [2]	Eight hours	25	123
			Short term	50	246
n-butanol, butan-1-ol	71-36-3	United Kingdom [2]	Eight hours		
			Short term	50	154
		United States [3] (Cal/OSHA)	Eight hours	(Ceiling) 50	
			Short term		
		United States [4] (NIOSH)	Eight hours	(Ceiling) 50	
			Short term		
2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	112-34-5	European Union [1]	Eight hours	10	67,5
			Short term	15	101,2
		United Kingdom [2]	Eight hours	10	67,5
			Short term	15	101,2
butanone, ethyl methyl ketone	78-93-3	European Union [1]	Eight hours	200	600
			Short term	300	900
		United Kingdom [2]	Eight hours	200	600
			Short term	300	899
		United States [3] (Cal/OSHA)	Eight hours	200	
			Short term	300	
		United States [4] (NIOSH)	Eight hours	200	
			Short term	300	
		United States [5] (OSHA)	Eight hours	200	590
			Short term		
N,N-dimethylethanolamine, 2-dimethylaminoethanol	108-01-0	United Kingdom [2]	Eight hours	2	7,4
			Short term	6	22

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

[3] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[4] According Compendium of Policy Documents and Statements adopted by National Institute for Occupational Safety and Health (NIOSH).

[5] According Occupational Health and Safety Standards and US Code of Federal Regulations adopted by US Occupational Safety and Health Administration (OSHA).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
2-butoxyethanol, butyl cellosolve, ethylene glycol monobutyl ether CAS No: 111-76-2 EC No: 203-905-0	DNEL (Workers)	Inhalation, Long-term, Systemic effects	98 (mg/m ³)
n-butanol, butan-1-ol CAS No: 71-36-3 EC No: 200-751-6	DNEL (Workers)	Inhalation, Long-term, Local effects	310 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Local effects	55 (mg/m ³)
	DNEL (General population)	Oral, Long-term, Systemic effects	3,125 (mg/kg bw/day)
2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether CAS No: 112-34-5 EC No: 203-961-6	DNEL (Workers)	Inhalation, Long-term, Local effects	67,5 (mg/m ³)
	DNEL (Workers)	Inhalation, Long-term, Systemic effects	67,5 (mg/m ³)
butanone, ethyl methyl ketone CAS No: 78-93-3 EC No: 201-159-0	DNEL (Workers)	Inhalation, Long-term, Systemic effects	600 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Systemic effects	106 (mg/m ³)

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



KLW-55-KANDY LISTO AL USO BASE AGUA - MAGENTA 55

Version: 2
Revision date: 12/02/2018

Page 6 of 13
Print date: 22/09/2018

	DNEL (Workers)	Dermal, Long-term, Systemic effects	1161 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	412 (mg/kg bw/day)
	DNEL (General population)	Oral, Long-term, Systemic effects	31 (mg/kg bw/day)
	DMEL (General population)	Inhalation, Long-term, Systemic effects	106 (mg/m ³)
	DMEL (General population)	Dermal, Long-term, Systemic effects	412 (mg/m ³)
N,N-dimethylethanolamine,2-dimethylaminoethanol CAS No: 108-01-0 EC No: 203-542-8	DNEL (Workers)	Inhalation, Long-term, Local effects	7,4 (mg/m ³)
	DNEL (Workers)	Inhalation, Long-term, Systemic effects	7,4 (mg/m ³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
n-butanol, butan-1-ol CAS No: 71-36-3 EC No: 200-751-6	aqua (freshwater)	0,082 (mg/L)
	aqua (marine water)	0,0082 (mg/L)
	aqua (intermittent releases)	2,25 (mg/L)
	PNEC STP	2476 (mg/L)
	sediment (freshwater)	0,178 (mg/kg sediment dw)
	sediment (marine water)	0,0178 (mg/kg sediment dw)
	soil	0,015 (mg/kg soil dw)
butanone, ethyl methyl ketone CAS No: 78-93-3 EC No: 201-159-0	aqua (freshwater)	55,8 (mg/L)
	aqua (marine water)	55,8 (mg/L)
	Soil	22,5 (mg/kg soil dw)
	aqua (intermittent releases)	55,8 (mg/L)
	PNEC STP	709 (mg/L)
	sediment (freshwater)	284,74 (mg/kg sediment dw)
	sediment (marine water)	284,7 (mg/kg sediment dw)
oral (Hazard for predators)	1000 (mg/kg food)	

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %
Uses:	Water base colors for airbrush painting
Breathing protection:	
If the recommended technical measures are observed, no individual protection equipment is necessary.	

-Continued on next page.-

SAFETY DATA SHEET




(in accordance with Regulation (EU) 2015/830)

KLW-55-KANDY LISTO AL USO BASE AGUA - MAGENTA 55



Version: 2
Revision date: 12/02/2018

Page 7 of 13
Print date: 22/09/2018

Hand protection:		
If the product is handled correctly, no individual protection equipment is necessary.		
Eye protection:		
PPE:	Face shield.	
Characteristics:	«CE» marking, category II. Face and eye protector against splashing liquid.	
CEN standards:	EN 165, EN 166, EN 167, EN 168	
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly.	
Observations:	Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.	
Skin protection:		
PPE:	Anti-static protective clothing.	
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.	
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5	
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.	
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.	
PPE:	Anti-static safety footwear.	
Characteristics:	«CE» marking, category II.	
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346	
Maintenance:	The footwear should be checked regularly	
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Liquid with characteristic odour
Colour: N.A./N.A.
Odour: AFRUTADO
Odour threshold: N.A./N.A.
pH: N.A./N.A.
Melting point: N.A./N.A.
Boiling Point: 100 °C
Flash point: 44 °C
Evaporation rate: N.A./N.A.
Inflammability (solid, gas): N.A./N.A.
Lower Explosive Limit: N.A./N.A.
Upper Explosive Limit: N.A./N.A.
Vapour pressure: 23,397
Vapour density: N.A./N.A.
Relative density: 0,981
Solubility: N.A./N.A.
Liposolubility: N.A./N.A.
Hydrosolubility: N.A./N.A.
Partition coefficient (n-octanol/water): N.A./N.A.
Auto-ignition temperature: N.A./N.A.
Decomposition temperature: N.A./N.A.
Viscosity: N.A./N.A.
Explosive properties: N.A./N.A.
Oxidizing properties: N.A./N.A.
N.A./N.A. = Not Available/Not Applicable due to the nature of the product

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

KLW-55-KANDY LISTO AL USO BASE AGUA - MAGENTA 55



Version: 2
Revision date: 12/02/2018

Page 8 of 13
Print date: 22/09/2018

9.2 Other information.

Pour point: N.A./N.A.

Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

If the storage conditions are satisfied, does not produce dangerous reactions.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

Flammable liquid and vapour.

10.4 Conditions to avoid.

Avoid the following conditions:

- High temperature.
- Static discharge.
- Contact with incompatible materials.
- Avoid temperatures near or above the flash point. Do not heat closed containers. Avoid direct sunlight and heat, as these may cause a risk of fire.

10.5 Incompatible materials.

Avoid the following materials:

- Explosives materials.
- Toxic materials.
- Oxidizing materials.

10.6 Hazardous decomposition products.

In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

SECTION 11: TOXICOLOGICAL INFORMATION.

2-butoxyethanol and its acetate are easily absorbed by the skin and can cause noxious effects to the kidneys.

IRRITANT PREPARATION. Splatters in the eyes can cause irritation.

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
n-butanol, butan-1-ol	Oral	LD50	Rat	4360 mg/kg bw [1]
	Dermal	LD50	Rabbit	3402 mg/kg bw [1]

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

KLW-55-KANDY LISTO AL USO BASE AGUA - MAGENTA 55



Version: 2
Revision date: 12/02/2018

Page 9 of 13
Print date: 22/09/2018

CAS No: 71-36-3 EC No: 200-751-6	Inhalation	[1] Union Carbide Corp. Bushy Run Research Center, Project Report No.14-73. Export, PA. 1951.
		LC50 Rat 7500 ppm (8 h) [1]
butanone,ethyl methyl ketone	Oral	LD50 Rat 2740 mg/kg bw [1] [1] Toxicology and Applied Pharmacology. Vol. 19, Pg. 699, 1971
	Dermal	LD50 Rabbit 6480 mg/kg bw [1] [1] Shell Chemical Company. Vol. MSDS-5390-4
	Inhalation	
CAS No: 78-93-3 EC No: 201-159-0		

a) acute toxicity;
Not conclusive data for classification.

Acute Toxicity Estimate (ATE):
Mixtures:
ATE (Dermal) = 14.329 mg/kg
ATE (Oral) = 4.961 mg/kg

b) skin corrosion/irritation;
Product classified:
Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;
Product classified:
Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;
Not conclusive data for classification.

e) germ cell mutagenicity;
Not conclusive data for classification.

f) carcinogenicity;
Not conclusive data for classification.

g) reproductive toxicity;
Not conclusive data for classification.

h) STOT-single exposure;
Based on available data, the classification criteria are not met.

i) STOT-repeated exposure;
Not conclusive data for classification.

j) aspiration hazard;
Not conclusive data for classification.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity
------	-------------

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

KLW-55-KANDY LISTO AL USO BASE AGUA - MAGENTA 55



Version: 2
Revision date: 12/02/2018

Page 10 of 13
Print date: 22/09/2018

	Type	Test	Kind	Value
n-butanol, butan-1-ol CAS No: 71-36-3 EC No: 200-751-6	Fish	LC50	Pimephales promelas	1376 mg/L (96 h) [1] [1] Wong, D.C.L, P.B. Dorn, and J.P. Salanitro. 1998. Aquatic Toxicity of Four Oxy-Solvents. Equilon Enterprises, LLC Technical Information Record WTC-3520.
	Aquatic invertebrates	EC50	Daphnia magna	1328 mg/L (48 h) [1] [1] Wong, D.C.L, P.B. Dorn, and J.P. Salanitro. 1998. Aquatic Toxicity of Four Oxy-Solvents. Equilon Enterprises, LLC Technical Information Record WTC-3520.
	Aquatic plants	EC90	Selenastrum capricornutum (Pseudokirchnerella subcapitata)	717 mg/L (96 h) [1] [1] Wong, D.C.L, P.B. Dorn, and J.P. Salanitro. 1998. Aquatic Toxicity of Four Oxy-Solvents. Equilon Enterprises, LLC Technical Information Record WTC-3520.
butanone, ethyl methyl ketone CAS No: 78-93-3 EC No: 201-159-0	Fish	LC50	Pimephales promelas	2993 mg/l (96 h) [1] [1] Experimental result, 1998.
	Aquatic invertebrates	LC50	Daphnia magna	8890 mg/l (24 h) [1] [1] Experimental result, 1977.
	Aquatic plants	EC50	Pseudokirchnerella subcapitata	2029 mg/l (96 h) [1] [1] OECD Guideline 201 (Alga, Growth Inhibition Test) reliability based in 2006 guideline.

12.2 Persistence and degradability.

There is no information available on the degradability of the substances present.

No information is available regarding the degradability of the substances present. No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
2-butoxyethanol, butyl cellosolve, ethylene glycol monobutyl ether N. CAS: 111-76-2 EC No: 203-905-0	0,8	-	-	Very low
n-butanol, butan-1-ol N. CAS: 71-36-3 EC No: 200-751-6	0,84	-	-	Very low
2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether N. CAS: 112-34-5 EC No: 203-961-6	0,56	-	-	Very low
butanone, ethyl methyl ketone	0,29	-	-	Very low

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

KLW-55-KANDY LISTO AL USO BASE AGUA - MAGENTA 55



Version: 2
Revision date: 12/02/2018

Page 11 of 13
Print date: 22/09/2018

N. CAS: 78-93-3	EC No: 201-159-0				
N,N-dimethylethanolamine,2-dimethylaminoethanol		-0,94	-	-	Very low
N. CAS: 108-01-0	EC No: 203-542-8				

12.4 Mobility in soil.

No information is available about the mobility in soil.
The product must not be allowed to go into sewers or waterways.
Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13 DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.
Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.

Transport document: Airway bill.

14.1 UN number.

UN No: UN1263

14.2 UN proper shipping name.

Description:

ADR: UN 1263, PAINT RELATED MATERIAL, 3, PG III, (D/E)

IMDG: UN 1263, PAINT RELATED MATERIAL, 3, PG III

ICAO/IATA: UN 1263, PAINT RELATED MATERIAL, 3, PG III

14.3 Transport hazard class(es).

Class(es): 3

14.4 Packing group.

Packing group: III

14.5 Environmental hazards.

Marine pollutant: No

14.6 Special precautions for user.

ADR LQ: 5 L

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)


KLW-55-KANDY LISTO AL USO BASE AGUA - MAGENTA 55



Version: 2
Revision date: 12/02/2018

Page 12 of 13
Print date: 22/09/2018

IMDG LQ: 5 L
ICAO LQ: 10 L



Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.
Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-E
Proceed in accordance with point 6.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)

Product Subcategory (Directive 2004/42/EC): Decorative effect coatings, water-borne

Phase I* (from 01/01/2007): 300 g/l

Phase II* (from 01/01/2010): 200 g/l

(*) g/l ready to use

VOC content (p/p): 11,799 %

VOC content: 115,762 g/l

The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Kind of pollutant for the water (Germany): WGK 1: Slightly hazardous for the water. (Autoclassified according to the AwSV Regulations)

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

KLW-55-KANDY LISTO AL USO BASE AGUA - MAGENTA 55



Version: 2
Revision date: 12/02/2018

Page 13 of 13
Print date: 22/09/2018

H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

Classification codes:

Acute Tox. 4 : Acute toxicity (Dermal), Category 4
Acute Tox. 4 : Acute toxicity (Inhalation), Category 4
Acute Tox. 4 : Acute toxicity (Oral), Category 4
Eye Dam. 1 : Serious eye damage, Category 1
Eye Irrit. 2 : Eye irritation, Category 2
Flam. Liq. 2 : Flammable liquid, Category 2
Flam. Liq. 3 : Flammable liquid, Category 3
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3
Skin Corr. 1B : Skin Corrosive, Category 1B
Skin Irrit. 2 : Skin irritant, Category 2

Sections changed compared with the previous version:

1,2,4,5,8,14,16

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
AwSV: Facility Regulations for handling substances that are hazardous for the water.
BCF: Bioconcentration factor.
CEN: European Committee for Standardization.
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
EC50: Half maximal effective concentration.
PPE: Personal protection equipment.
IATA: International Air Transport Association.
ICAO: International Civil Aviation Organization.
IMDG: International Maritime Code for Dangerous Goods.
LC50: Lethal concentration, 50%.
LD50: Lethal dose, 50%.
Log Pow: Logarithm of the partition octanol-water.
NOEC: No observed effect concentration.
PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.
WGK: Water hazard classes.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.