

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



Version: 2  
Revision date: 22/09/2018

Page 1 of 11  
Print date: 22/09/2018

## SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

### 1.1 Product identifier.

Product Name: Masilla Fiber  
Product Code: MSL-FB

### 1.2 Relevant identified uses of the mixture and uses advised against.

Surface fillers in painting process

#### Uses advised against:

Uses other than those recommended.

### 1.3 Details of the supplier of the safety data sheet.

Company: **CUSTOM CREATIVE**  
Address: C/ SEVILLA 43  
City: JEREZ DE LA FRONTERA  
Province: CADIZ  
Telephone: (+34) 956045939  
E-mail: info@customcreative.es  
Web: customcreative.es

**1.4 Emergency telephone number:** (+34) 956045939 (Only available during office hours; Monday-Friday; 08:00-18:00)

## SECTION 2: HAZARDS IDENTIFICATION.

### 2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

- Eye Irrit. 2 : Causes serious eye irritation.
- Flam. Liq. 3 : Flammable liquid and vapour.
- Repr. 2 : Suspected of damaging the unborn child.
- STOT RE 1 : Causes damage to organs through prolonged or repeated exposure.
- Skin Irrit. 2 : Causes skin irritation.

### 2.2 Label elements.

#### Labelling in accordance with Regulation (EU) No 1272/2008:

##### Pictograms:



Signal Word:

**Danger**

H statements:

- |       |   |
|-------|---|
| H226  | Flammable liquid and vapour.                                    |
| H315  | Causes skin irritation.   |
| H319  | Causes serious eye irritation.                                  |
| H361d | Suspected of damaging the unborn child.                         |
| H372  | Causes damage to organs through prolonged or repeated exposure. |

P statements:

- |      |  |
|------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P260 | Do not breathe dust/fume/gas/mist/vapours/spray.   |

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## MSL-FB-Masilla Fiber

Version: 2  
Revision date: 22/09/2018

Page 2 of 11  
Print date: 22/09/2018

P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352 IF ON SKIN: Wash with plenty of water/...  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 IF exposed or concerned: Get medical advice/attention.

Contains:  
styrene

### 2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

### 3.1 Substances.

Not Applicable.

### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
CAS No: 14807-96-6 EC No: 238-877-9	[1] Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	75 - 100 %	-	-
Index No: 601-026-00-0 CAS No: 100-42-5 EC No: 202-851-5 Registration No: 01-2119457861-32-XXXX	[1] styrene	10 - 25 %	Acute Tox. 4 *, H332 - Eye Irrit. 2, H319 - Flam. Liq. 3, H226 - Repr. 2, H361d - STOT RE 1, H372(órganos de audición) - Skin Irrit. 2, H315	-

(\*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

\* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a Community workplace exposure limit (see section 8.1).

## SECTION 4: FIRST AID MEASURES.

**IRRITANT PREPARATION.** Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

### 4.1 Description of first aid measures.

Delayed effects may occur after the exposure to the product.

#### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

#### Eye contact.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## MSL-FB-Masilla Fiber

**Version: 2**  
**Revision date: 22/09/2018**

**Page 3 of 11**  
**Print date: 22/09/2018**

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

### **Skin contact.**

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

### **Ingestion.**

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

### **4.2 Most important symptoms and effects, both acute and delayed.**

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

Long-term chronic exposure may result in injury to certain organs or tissues.

### **4.3 Indication of any immediate medical attention and special treatment needed.**

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Keep the person comfortable. Turn him/her over to the left side and stay there while waiting for medical care.

## **SECTION 5: FIREFIGHTING MEASURES.**

Flammable product, the necessary prevention measures should be taken in order to avoid risks, In case of fire, the following measures are recommended:

### **5.1 Extinguishing media.**

#### **Suitable extinguishing media:**

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

#### **Unsuitable extinguishing media:**

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

### **5.2 Special hazards arising from the mixture.**

#### **Special risks.**

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

### **5.3 Advice for firefighters.**

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

#### **Fire protection equipment.**

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES.**

### **6.1 Personal precautions, protective equipment and emergency procedures.**

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## MSL-FB-Masilla Fiber

Version: 2  
Revision date: 22/09/2018

Page 4 of 11  
Print date: 22/09/2018

### 6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

### 6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.  
For later elimination of waste, follow the recommendations under section 13.

## SECTION 7: HANDLING AND STORAGE.

### 7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

### 7.3 Specific end use(s).

Not available.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

### 8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m <sup>3</sup>
Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	14807-96-6	United Kingdom [1]	Eight hours		1
			Short term		
styrene	100-42-5	United Kingdom [1]	Eight hours	100	430
			Short term	250	1080
		United States [2] (Cal/OSHA)	Eight hours	50	
			Short term	100 (Ceiling) 500	
		United States [3] (NIOSH)	Eight hours	50	
			Short term	100	
United States	Eight hours	100			

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## MSL-FB-Masilla Fiber

Version: 2  
Revision date: 22/09/2018

Page 5 of 11  
Print date: 22/09/2018

		[4] (OSHA)	<b>Short term</b>	200 Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift: 600 [5 min in any 3 hr]	
--	--	------------	-------------------	---	--

[1] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

[2] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[3] According Compendium of Policy Documents and Statements adopted by National Institute for Occupational Safety and Health (NIOSH).

[4] According Occupational Health and Safety Standards and US Code of Federal Regulations adopted by US Occupational Safety and Health Administration (OSHA).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
styrene CAS No: 100-42-5 EC No: 202-851-5	DNEL (Workers)	Inhalation, Long-term, Systemic effects	85 (mg/m <sup>3</sup> )




DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

### 8.2 Exposure controls.

#### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

<b>Concentration:</b>	<b>100 %</b>		
<b>Uses:</b>	<b>Surface fillers in painting process</b>		
<b>Breathing protection:</b>			
PPE:	Filter mask for protection against gases and particles.		
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.		
CEN standards:	EN 136, EN 140, EN 405		
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.		
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed:	A2		
<b>Hand protection:</b>			
PPE:	Non-disposable protective gloves against chemicals.		
Characteristics:	«CE» marking, category III. Check the list of chemicals for which the glove has been tested.		
CEN standards:	EN 374-1, EN 374-2, EN 374-3, EN 420		
Maintenance:	A schedule for the periodical replacement of gloves should be established in order to guarantee their replacement before pollutants permeate them. The use of contaminated gloves could be more dangerous than not using gloves, since the pollutant can gradually accumulate in the glove's material.		
Observations:	They are to be replaced whenever tears, cracks or deformations are observed or when exterior dirt could reduce their strength.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480
		Material thickness (mm):	0,35
<b>Eye protection:</b>			
PPE:	Protective goggles with built-in frame.		
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against splashing liquid, dust, smoke, fog and vapour.		

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## MSL-FB-Masilla Fiber

Version: 2  
Revision date: 22/09/2018

Page 6 of 11  
Print date: 22/09/2018

CEN standards:	EN 165, EN 166, EN 167, EN 168	
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.	
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.	
<b>Skin protection:</b>		
PPE:	Chemical protective clothing	
Characteristics:	«CE» marking, category III. Clothing should fit properly. The level of protection must be set according to a test parameter called BT (Breakthrough Time), which indicates how long it takes for the chemical to pass through the material.	
CEN standards:	EN 464, EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034	
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.	
Observations:	The protective clothing's design should facilitate correct positioning, staying in place without moving for the period of use expected, bearing in mind environmental factors as well as any movement or position the user might adopt while carrying out the activity.	
PPE:	Anti-static safety footwear against chemicals.	
Characteristics:	«CE» marking, category III. Check the list of chemicals against which the footwear is resistant.	
CEN standards:	EN ISO 13287, EN 13832-1, EN 13832-2, EN 13832-3, EN ISO 20344, EN ISO 20345	
Maintenance:	For correct maintenance of this kind of safety footwear, it is necessary to observe the instructions specified by the manufacturer. The footwear should be replaced as soon as any sign of damage is observed.	
Observations:	The footwear should be cleaned regularly and dried when damp, although it should not be placed too close to a source of heat in order to avoid any sharp changes in temperature.	

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

#### 9.1 Information on basic physical and chemical properties.

Appearance: N.A./N.A.  
Colour: N.A./N.A.  
Odour: N.A./N.A.  
Odour threshold: N.A./N.A.  
pH: N.A./N.A.  
Melting point: N.A./N.A.  
Boiling Point: 145 °C  
Flash point: 32 °C  
Evaporation rate: N.A./N.A.  
Inflammability (solid, gas): N.A./N.A.  
Lower Explosive Limit: N.A./N.A.  
Upper Explosive Limit: N.A./N.A.  
Vapour pressure: 1,496  
Vapour density: N.A./N.A.  
Relative density: 1,82  
Solubility: N.A./N.A.  
Liposolubility: N.A./N.A.  
Hydrosolubility: N.A./N.A.  
Partition coefficient (n-octanol/water): N.A./N.A.  
Auto-ignition temperature: N.A./N.A.  
Decomposition temperature: N.A./N.A.  
Viscosity: N.A./N.A.  
Explosive properties: N.A./N.A.  
Oxidizing properties: N.A./N.A.  
N.A./N.A. = Not Available/Not Applicable due to the nature of the product

#### 9.2 Other information.

Pour point: N.A./N.A.  
Blink: N.A./N.A.  
Kinematic viscosity: N.A./N.A.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



**Version: 2**  
**Revision date: 22/09/2018**

**Page 7 of 11**  
**Print date: 22/09/2018**

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

## SECTION 10: STABILITY AND REACTIVITY.

### 10.1 Reactivity.

If the storage conditions are satisfied, does not produce dangerous reactions.

### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

### 10.3 Possibility of hazardous reactions.

Flammable liquid and vapour.

### 10.4 Conditions to avoid.

Avoid the following conditions:

- High temperature.
- Static discharge.
- Contact with incompatible materials.
- Avoid temperatures near or above the flash point. Do not heat closed containers. Avoid direct sunlight and heat, as these may cause a risk of fire.

### 10.5 Incompatible materials.

Avoid the following materials:

- Explosives materials.
- Toxic materials.
- Oxidizing materials.

### 10.6 Hazardous decomposition products.

In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

## SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT PREPARATION. Splatters in the eyes can cause irritation.

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

### 11.1 Information on toxicological effects.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Product classified:

Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;

Product classified:

Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## MSL-FB-Masilla Fiber

**Version: 2**  
**Revision date: 22/09/2018**

**Page 8 of 11**  
**Print date: 22/09/2018**

f) carcinogenicity;  
Not conclusive data for classification.

g) reproductive toxicity;  
Product classified:  
Reproductive toxicant, Category 2: Suspected of damaging fertility or the unborn child.

h) STOT-single exposure;  
Not conclusive data for classification.

i) STOT-repeated exposure;  
Product classified:  
Specific target organ toxicity following a repeated exposure, Category 1: Causes damage to organs through prolonged or repeated exposure.

j) aspiration hazard;  
Not conclusive data for classification.

### SECTION 12: ECOLOGICAL INFORMATION.

#### 12.1 Toxicity.

There is no information available on the biodegradability of the substances present.

#### 12.2 Persistence and degradability.

There is no information available on the degradability of the substances present.  
No information is available regarding the degradability of the substances present. No information is available about persistence and degradability of the product.

#### 12.3 Bioaccumulative potential.

**Information about the bioaccumulation of the substances present.**

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
styrene N. CAS: 100-42-5      EC No: 202-851-5	3,05	-	-	Moderate

#### 12.4 Mobility in soil.

No information is available about the mobility in soil.  
The product must not be allowed to go into sewers or waterways.  
Prevent penetration into the ground.

#### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

#### 12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

### SECTION 13 DISPOSAL CONSIDERATIONS.

#### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

-Continued on next page.-



# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



**Version: 2**  
**Revision date: 22/09/2018**

**Page 9 of 11**  
**Print date: 22/09/2018**

Follow the provisions of Directive 2008/98/EC regarding waste management.

## SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

**Land:** Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

**Sea:** Transport by ship: IMDG.

Transport documentation: Bill of lading

**Air:** Transport by plane: ICAO/IATA.

Transport document: Airway bill.

### 14.1 UN number.

UN No: UN3269

### 14.2 UN proper shipping name.

Description:

ADR: UN 3269, POLYESTER RESIN KIT, 3, PG III, (E)

IMDG: UN 3269, POLYESTER RESIN KIT, 3, PG III (32°C)

ICAO/IATA: UN 3269, POLYESTER RESIN KIT, 3, PG III

### 14.3 Transport hazard class(es).

Class(es): 3

### 14.4 Packing group.

Packing group: III

### 14.5 Environmental hazards.

Marine pollutant: No

### 14.6 Special precautions for user.

Labels: 3



Hazard number: Not applicable.

ADR LQ: 5 L

IMDG LQ: 5 L

ICAO LQ: Not applicable.

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E, S-D

Proceed in accordance with point 6.

### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

## SECTION 15: REGULATORY INFORMATION.

### 15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## MSL-FB-Masilla Fiber

**Version: 2**  
**Revision date: 22/09/2018**

**Page 10 of 11**  
**Print date: 22/09/2018**

### Volatile organic compound (VOC)

Product Subcategory (Directive 2004/42/EC): Bodyfiller/stopper (All types)

Phase I\* (from 01/01/2007): 250 g/l

Phase II\* (from 01/01/2010): 250 g/l

(\* ) g/l ready to use

VOC content (p/p): 20 %

VOC content: 46 g/l

The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Kind of pollutant for the water (Germany): WGK 2: Hazardous for the water. (Autoclassified according to the AwSV Regulations)

### **15.2 Chemical safety assessment.**

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## **SECTION 16: OTHER INFORMATION.**

Complete text of the H phrases that appear in section 3:

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>. (órganos de audición)

Classification codes:

Acute Tox. 4 : Acute toxicity (Inhalation), Category 4

Eye Irrit. 2 : Eye irritation, Category 2

Flam. Liq. 3 : Flammable liquid, Category 3

Repr. 2 : Reproductive toxicant, Category 2

STOT RE 1 : Specific target organ toxicity following a repeated exposure, Category 1

Skin Irrit. 2 : Skin irritant, Category 2

Sections changed compared with the previous version:

1,4,16

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AwSV: Facility Regulations for handling substances that are hazardous for the water.

BCF: Bioconcentration factor.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## MSL-FB-Masilla Fiber

**Version: 2**

**Revision date: 22/09/2018**

**Page 11 of 11**

**Print date: 22/09/2018**

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.  
EC50: Half maximal effective concentration.  
PPE: Personal protection equipment.  
IATA: International Air Transport Association.  
ICAO: International Civil Aviation Organization.  
IMDG: International Maritime Code for Dangerous Goods.  
LC50: Lethal concentration, 50%.  
LD50: Lethal dose, 50%.  
Log Pow: Logarithm of the partition octanol-water.  
NOEC: No observed effect concentration.  
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.  
WGK: Water hazard classes.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.